PacifiCorp

Updated December 11, 2025

These EVSE meet the program requirements established by PacifiCorp. All hardware must have a minimum 3-year warranty.

All qualifying EVSE hardware must be paired with an approved third-party network service.

Residential

Brand	Model	Model Name	Type	Max Power (kW)	Notes	[1-3] Power Quality
Autel	MAXI US AC LW12	AC Lite	AC	12	Single port. NEMA 14-50 plug. Separate holster.	✔
Autel	MAXI US AC W12	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.	✔
Autel	MAXI US AC W12-H	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.	✔
Autel	Maxi UW19LB02	MaxiCharger AC 80A	AC	19.2	Single port.	✔
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	Dual Port, Standalone network capability	✔
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability	✔
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	Single or dual Port, Standalone network capability	✔
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability	✔
ChargePoint	CT40##-GW1-*****##	CT4000	AC	7.2	CT4000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 30A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 5.7" Display, Contactless Credit Card and RFID Reader	✔
ChargeTronix	UP160J-#MP-###	UP160J	AC	7.2	Dual Port, Must acquire Gateway for network connectivity	✔
ChargeTronix	UP80J-#MP-###	UP80J	AC	7.2	Single Port, Must acquire Gateway for network connectivity	✔
Chargie	CH-L-48-PRA-1-18		AC	11.52		✔
Chargie	CH-L-48-PRA-1-18-32		AC	7.68		✔
Chargie	CH-L-48-PRA-1-18-40		AC	9.6		✔
Chargie	CH-L-48-PRA-1-25		AC	11.52		✔
Chargie	CH-L-48-PRA-1-25-32		AC	7.68		✔
Chargie	CH-L-48-PRA-1-25-40		AC	9.6		✔
Chargie	CH-L-48-PRAC-1-18		AC	11.52		✔
Chargie	CH-L-48-PRAC-1-18-32		AC	7.68		✔
Chargie	CH-L-48-PRAC-1-18-40		AC	9.6		✔
Chargie	CH-L-48-PRAC-1-25		AC	11.52		✔
Chargie	CH-L-48-PRAC-1-25-32		AC	7.68		✔
Chargie	CH-L-48-PRAC-1-25-40		AC	9.6		✔
Chargie	CH-L-48-PRACT-1-18		AC	11.52		✔
Chargie	CH-L-48-PRACT-1-18-32		AC	7.68		✔
Chargie	CH-L-48-PRACT-1-18-40		AC	9.6		✔
Chargie	CH-L-48-PRACT-1-25		AC	11.52		✔
Chargie	CH-L-48-PRACT-1-25-32		AC	7.68		✔
Chargie	CH-L-48-PRACT-1-25-40		AC	9.6		✔
Chargie	CH-L-48-PRAT-1-18		AC	11.52		✔
Chargie	CH-L-48-PRAT-1-18-32		AC	7.68		✔
Chargie	CH-L-48-PRAT-1-18-40		AC	9.6		✔
Chargie	CH-L-48-PRAT-1-25		AC	11.52		✔
Chargie	CH-L-48-PRAT-1-25-32		AC	7.68		✔
Chargie	CH-L-48-PRAT-1-25-40		AC	9.6		✔
Eaton	CT40##-GW1-*****##-ETN	CT4000	AC	7.2	CT4000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 30A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 5.7" Display, Contactless Credit Card and RFID Reader	✔
Emporia	EMEVSE1	EV Charger	AC	11.52		✔
Epic Charging	EC48-AC	Epic48	AC	11.5	Single Port, Standalone network capability	✔
Epic Charging	EC80-AC	Epic80	AC	19.2	Single Port, Standalone network capability	✔
Epic Charging	ECB48-AC	Epic48	AC	11.5	Single Port, Standalone network capability	✔
Epic Charging	ECB80-AC	Epic80	AC	19.2	Single Port, Standalone network capability	✔
EVBolt	EVB-AC-PAX19	Prestige 19	AC	19.1	Single Port, Standalone network capability	✔
EVGateway	EGW-#C-32-#		AC	7.7		✔
EVGateway	EGW-#C-40-#		AC	9.6		✔
EVGateway	EGW-#C-48-#		AC	11.5		✔
EVGateway	EGW-EX-1193-#		AC	19.2		✔
EvoCharge	EVC5001####	EVC5001####	AC	12	Single port.	✔
EVPassport	Rosa Charger	Rosa	AC	11	Single Port, Standalone network capability	✔
Ford Pro Charging	FPC-AC0048ZC-###	Ford Pro AC Charging Station, 48A Series 2	AC	11.5	Single Port.	✔
Ford Pro Charging	FPC-AC0080ZC-U##	Ford Pro AC Charging Station, Series 2	AC	19.2	Single Port NRTL Listed as EX-1193-1	✔
Generac Power Systems	PUP2-U-1-5-N-GC2	40A Level 2 Plus	AC	9.6	Single Port	✔
InCharge	EX-1193-1		AC	19.2	Single Port NRTL Listed as EX-1193-1	✔
Loop Global	EVS-32A-L2-001	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability	✔
Loop Global	EVS-32A-L2-002	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability	✔
Loop Global	EVS-80A-L2-001	EV-Fleet	AC	19.2	SAE J1772, Standalone network capability	✔
Loop Global	EVS-80A-L2-002	EV-Fleet	AC	19.2	SAE J1772, Standalone network capability	✔
Noodoe	AC11P/ AC11P Exceed		AC	11.5	Single port.	✔
OpConnect	IC80	IC80	AC	19.2	Single Port NRTL Listed as EX-1193-1	✔
OpConnect	SC80	SC80	AC	19.2	Single Port NRTL Listed as EX-1193-3	✔
PowerFlex Systems	JNT-EVC10 (PF-JT48)		AC	11.52	Must acquire Nexus	✔

RAB Lighting Inc.	EVC48	EVC48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00	✔
TECO-Westinghouse	AWLU770001/ AW32		AC	7.7	Single Port, Standalone network capability	✔
Tellus Power	UP160J-#MP-###		AC	7.2	Dual Port, Must acquire Gateway for network connectivity	✔
Tellus Power	UP80J-#MP-###		AC	7.2	Single Port, Must acquire Gateway for network connectivity	✔
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-W EVP1100-WG/CPEVAC-11KW-J17-WG CPEVAC-11KW-S18-#		AC	11.4	Single Port	✔
TurnOnGreen	EVP700-W/CPEVAC-7KW-J17-W/ EVP700-G/CPEVAC-7KW-J17-G CPEVAC-7KW-S17-#		AC	7.6	Single Port	✔
Wallbox	PUP1-#-1-5-#-### / PUP2-#-1-5-#-###	Pulsar Plus	AC	9.6	Single Port	✔

Commercial

Brand	Model	Model Name	Type	Max Power (kW)	Notes
Alpitronic	HYC400-2	Hypercharger	DC	200	1-4 Ports
Alpitronic	HYC400-3	Hypercharger	DC	300	1-4 Ports
Alpitronic	HYC400-4	Hypercharger	DC	400	1-4 Ports
Autel	AC W12-L-4G	AC Elite	AC	12	Single Port ; OCPP Full Certificate with software version V1.13.97
Autel	DC HiPower	DC HiPower	DC	640	The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	MaxiCharger DH480	MaxiCharger DH480	DC	480	Dual or quad port.
Autel	MaxiCharger DH400	MaxiCharger DH400	DC	400	Dual or quad port.
Autel	MaxiCharger DH360	MaxiCharger DH360	DC	360	Dual or quad port.
Autel	MaxiCharger DH300	MaxiCharger DH300	DC	300	Dual or quad port.
Autel	Maxi UW19C002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19CJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	Maxi UW19L002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19LJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	UF####101	AC Ultra	AC	19.2	Single Port or Dual Port
Autel	UF160A4001	Maxicharger DC Fast 160kW	DC	160	Single or dual port
Autel	UF180A4001	Maxicharger DC Fast 180kW	DC	180	Single or dual port
Autel	UF200A4001	Maxicharger DC Fast 200kW	DC	200	Single or dual port
Autel	UF220A4001	Maxicharger DC Fast 220kW	DC	220	Single or dual port
Autel	UF240A4001	Maxicharger DC Fast 240kW	DC	240	Single or dual port
Autel	UW12-J0610CA0002	MaxiCharger AC Single	AC	12	Single port.
Autel	UW12-J0650CA0002	MaxiCharger AC Single	AC	12	Single port.
Blink	780	Series 7 ISO Single	AC	19.2	Single port.
Blink	01-0568	Blink 300kW	DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0569	Blink 360kW	DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0578	Blink 180kW	DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0581	Blink 240kW	DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	200-000320-A	Blink 200kW	DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	Dual Port, Standalone network capability
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	780 Series	Series 7 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	Single or dual Port, Standalone network capability
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	880 (80A)	Series 8 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	C50######## C80########	C-Series	DC	600	Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser ouputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
Blink	IQW2-80U-M1-R2-N-25 (Advanced-LTE) Part Number 01-0207-LTE (IQ 200 Advanced)	IQ 200 Advanced	AC	19.2	Single Port
Blink	IQW2-80U-M3-R3-N-25 (Advanced-LTE-W) Part Number 01-0207-LTE	IQ 200 Advanced	AC	19.2	Single Port
BTC Power	HPCD6-500-05-005		DC	360	Can power up to 4 dual port Fleet Dispensers to 1 Power Cabinet and charge sequentially. can charge up to 8 vehicles sequentially as a result.
BTC Power	HPCD7-350-###-01#	Gen4 Public Dispenser	DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
BTC Power	HPCT3-###-480-# / HPCD7-500-###-01#	Gen4 Public Dispenser	DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
CHAEVI	CV-3FD150P-IUL3	SONIC (150kW) (3 Phase, 3 Wire)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL3	SONIC (180kW) (3 Phase, 3 Wire)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL	SONIC (150kW) (3 Phase, 4 Wire)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL	SONIC (180kW) (3 Phase, 4 Wire)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3UD403P-NCC3 (CCS1/CCS1)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable

CHAEVI	CV-3UD403P-NCN3 (CCS1/NACS)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	CV-3UD403P-NDN3 (NACS/NACS)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	DCV-3FD150-ICN	DUOCONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD180-ICN	DUOCONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
ChargePoint	CP6####-50A-L##	6000 Series	AC	12	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CP6####-80A-L##	6000 Series	AC	19.2	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DC	160	[Paired Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPF50- L##-******	CPF50	AC	12	CPF50 family, Single or Dual Port, Pedestal or Wall Mount, 50A, Type 1, Cable 18' or 23', Single Phase Charger, Cable Management Kit optional
ChargePoint	CT40##-GW1-*****##	CT4000	AC	7.2	CT4000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 30A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 5.7" Display, Contactless Credit Card and RFID Reader
ChargePoint	Express Plus 1000 Power Block: CPPB0001*** PM1.5 43-001200-** EXPP-PL10##*-#*#*#-#*#*#-***	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 1000 series; Used for Fleet or Commercial.
ChargePoint	Express Plus 2000 (EXPP-PL20##-CHIP)	Express Plus	DC	500	[CHIP sku]Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connctor including CCS, NACS, or CHAdeMO
ChargePoint	Express Plus 2000 (EXPP-PL20##-FHWA)	Express Plus	DC	500	[FHWA sku] Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connctor including CCS, NACS, or CHAdeMO
ChargePoint	Express Plus 2000 (EXPP-PL20##)	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connctor including CCS, NACS, or CHAdeMO
CyberSwitching	CSE1-WIFI-BL	CSE1	AC	11.5	Single Port
Epic Charging	EC48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	EC80-AC	Epic80	AC	19.2	Single Port, Standalone network capability
EverCharge	E800-1042-01	DCFC 320kW All-in-One, w/ Dual CCS1	DC	320	Dual port.
EverCharge	EV002-48,E800-1000	EV02	AC	11.52	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-32A	EV02	AC	7.68	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-40A	EV02	AC	8.3	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001	EV02	AC	19.2	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001-40A	EV02	AC	8.3	Single Port, Standalone network capability
EVSIS	JC-94F2-350-0T5	DC Charger 350kW	DC	350	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-94F2-400-0T5	DC Charger 400kW	DC	400	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-180-CT	DC Charger 180kW	DC	180	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-240-CT	DC Charger 240kW	DC	240	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
FLO	Ultra	Ultra	DC	320	Dual port.
Gravity	GR-LH500CX		DC	500	
Gravity	GT-AH200XX		DC	200	
Gravity	GT-AV200XX		DC	200	
Gravity	GT-LAV500EX		DC	500	
Gravity	GT-LLH500EX		DC	500	
Gravity	GT-LV500CX		DC	500	
Loop Global	EVS-32A-L2-001	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability
Loop Global	EVS-32A-L2-002	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability
Loop Global	EVS-80A-L2-001	EV-Fleet	AC	19.2	SAE J1772, Standalone network capability
Loop Global	EVS-80A-L2-002	EV-Fleet	AC	19.2	SAE J1772, Standalone network capability
Loop Global	EVS-FLASH-300-D01	Infinity Flash (with screen)	DC	300	Dual port with screen. Power cabinet required: EVS-FLASH- 360-PC01
Loop Global	EVS-FLASH-300-D01-150	Infinity Flash (with screen)(derated)	DC	150	150kW max per port
Loop Global	EVS-FLASH-300-D02	Infinity Flash (without screen)	DC	300	Dual port without screen. Power cabinet required: EVS-FLASH- 360-PC01
Loop Global	EVS-FLASH-300-D02-150	Infinity Flash (without screen)(derated)	DC	150	150kW max per port
Noodoe	AC11P/ AC11P Exceed		AC	11.5	Single port.
OpConnect	IC80	IC80	AC	19.2	Single Port NRTL Listed as EX-1193-1
OpConnect	SC80	SC80	AC	19.2	Single Port NRTL Listed as EX-1193-3
PowerPump	AC550	AC550	AC	10	Single Port.

Sinexcel	SEC1000/160Y-H-U ; SEC1000/160Y-T-U	SEC160	DC	160	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/240Y-H-USEC1000/240Y-HH-U	SEC 240	DC	240	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/360F-N-USEC1000/480F-N-US	SEC 480	DC	480	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Air cooling output 350A Liquid cooling sustained maximum output 500A
StarCharge	AC###AN030######	Artemis	AC	19.2	Single port.
StarCharge	DC3200AN147XYZ/ DC2800AN147XYZ/	Titan 320kW	DC	320	Dual port.
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-WEVP1		AC	11.4	Single Port
TurnOnGreen	EVP700-W/CPEVAC-7KW-J17-W/EVP700		AC	7.6	Single Port
Zerova	AXLU111001/AX48	AX48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Zerova	AXLU191001/AX80	AX80	AC	19.1	Single Port, Standalone network capability
Zerova	DQ480: DQWU482/DQWA482	DQ Series: DQ480	DC	480	Configurable to four or two cables
Zerova	DQWA242	DQ240	DC	240	Configurable to four or two cables
Zerova	DQWA360	DQ360	DC	360	Configurable to four or two cables
Zerova	DT240: DTWA240	DT Series: DT240	DC	240	Configurable to four or two cables
Zerova	DZ480: DZWU482/DEZWA482	DZ Series: DZ480	DC	480	Configurable to two, four, or six cables

Fleet

Brand	Model	Model Name	Type	Max Power (kW)	Notes
Alpitronic	HYC400-1	Hypercharger	DC	100	1-4 Ports
Alpitronic	HYC400-2	Hypercharger	DC	200	1-4 Ports
Alpitronic	HYC400-3	Hypercharger	DC	300	1-4 Ports
Alpitronic	HYC400-4	Hypercharger	DC	400	1-4 Ports
Alpitronic	HYC50	Hypercharger	DC	50	1-2 Ports
Autel	AC W12-L-4G	AC Elite	AC	12	Single Port ; OCPP Full Certificate with software version V1.13.97
Autel	DC HiPower	DC HiPower	DC	640	The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	MaxiCharger DH480	MaxiCharger DH480	DC	480	Dual or quad port.
Autel	MaxiCharger DH400	MaxiCharger DH400	DC	400	Dual or quad port.
Autel	MaxiCharger DH360	MaxiCharger DH360	DC	360	Dual or quad port.
Autel	MaxiCharger DH300	MaxiCharger DH300	DC	300	Dual or quad port.
Autel	MAXI US AC LW12	AC Lite	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	MAXI US AC W12	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	MAXI US AC W12-H	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	Maxi UW19C002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19CJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	Maxi UW19L002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19LB02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	Maxi UW19LJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	UF####001	AC Ultra	AC	19.2	Single Port or Dual Port. No credit card reader
Autel	UF####101	AC Ultra	AC	19.2	Single Port or Dual Port
Autel	UF060A3001	Maxicharger DC Fast 60kW	DC	60	Single or dual port
Autel	UF080A3001	Maxicharger DC Fast 80kW	DC	80	Single or dual port
Autel	UF100A3001	Maxicharger DC Fast 100kW	DC	100	Single or dual port
Autel	UF120A3001	Maxicharger DC Fast 120kW	DC	120	Single or dual port
Autel	UF140A4001	Maxicharger DC Fast 140kW	DC	140	Single or dual port
Autel	UF160A4001	Maxicharger DC Fast 160kW	DC	160	Single or dual port
Autel	UF180A4001	Maxicharger DC Fast 180kW	DC	180	Single or dual port
Autel	UF200A4001	Maxicharger DC Fast 200kW	DC	200	Single or dual port
Autel	UF220A4001	Maxicharger DC Fast 220kW	DC	220	Single or dual port
Autel	UF240A4001	Maxicharger DC Fast 240kW	DC	240	Single or dual port
Autel	UW12-J0610CA0002	MaxiCharger AC Single	AC	12	Single port.
Autel	UW12-J0650CA0002	MaxiCharger AC Single	AC	12	Single port.

Blink	780	Series 7 ISO Single	AC	19.2	Single port.
Blink	01-0202 (MQ200)	MQ200	AC	12	Single Port; NRTL listed as LiteOn MQW2-50C-M2-R#-#-23 and HQW2-50C-#-N#-#-23
Blink	01-0568	Blink 300kW	DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0569	Blink 360kW	DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0578	Blink 180kW	DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0581	Blink 240kW	DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	200-000320-A	Blink 200kW	DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	Dual Port, Standalone network capability
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	780 Series	Series 7 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	Single or dual Port, Standalone network capability
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	880 (80A)	Series 8 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	C50######## C80########	C-Series	DC	600	Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser ouputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
Blink	IQW2-80U-M1-R2-N-25 (Advanced-LTE) Part Number 01-0207-LTE (IQ200 Advanced)	IQ200 Advanced	AC	19.2	Single Port
BTC Power	HPCD6-500-05-005		DC	360	Can power up to 4 dual port Fleet Dispensers to 1 Power Cabinet and charge sequentially. can charge up to 8 vehicles sequentially as a result.
BTC Power	HPCD7-350-###-01#	Gen4 Public Dispenser	DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
BTC Power	HPCT3-###-480-# / HPCD7-500-###-01#	Gen4 Public Dispenser	DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
CHAEVI	CV-3FD120P-IUL3	SONIC (120kW) (3 Phase, 3 Wire)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL3	SONIC (150kW) (3 Phase, 3 Wire)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL3	SONIC (180kW) (3 Phase, 3 Wire)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD120P-IUL	SONIC (120kW) (3 Phase, 4 Wire)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL	SONIC (150kW) (3 Phase, 4 Wire)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL	SONIC (180kW) (3 Phase, 4 Wire)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3UD403P-NCC3 (CCS1/CCS1)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	CV-3UD403P-NCN3 (CCS1/NACS)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	CV-3UD403P-NDN3 (NACS/NACS)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	DCV-3FD120-ICN	DUOCONIC (120kW)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD150-ICN	DUOCONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD180-ICN	DUOCONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
ChargePoint	CP6####-50A-L##	6000 Series	AC	12	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CP6####-80A-L##	6000 Series	AC	19.2	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CPE250C-625-CCS1-200A-****	Express 250	DC	62.5	ChargePoint Express 250 Station (62.5 kW) - includes Express 250 Station, 2x Power Modules, 1x CCS1 200A cable, 1x CHAdeMO cable or NACS, North America Modem/SIM, cUL and UL listed, requires CPE250-CMT-IMPERIAL in US, CPE250-CMT-METRIC in Canada. CPE250-CMT-IMPERIAL/METRIC not included. FWHA and FTA compliant models available as well as with integrated EMV Chip Reader terminal.
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DC	160	[Paired Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DC	80	[Single Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.

ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DC	80	[Single Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DC	80	[Single Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPF50- L##-******	CPF50	AC	12	CPF50 family, Single or Dual Port, Pedestal or Wall Mount, 50A, Type 1, Cable 18' or 23', Single Phase Charger, Cable Management Kit optional
ChargePoint	CT40##-GW1-*****##	CT4000	AC	7.2	CT4000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 30A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 5.7" Display, Contactless Credit Card and RFID Reader
ChargePoint	Express Plus 1000 Power Block: CPPB0001*** PM1.5 43-001200-** EXPP-PL10##*-#*#*#-#*#*#-***	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 1000 series; Used for Fleet or Commercial.
ChargePoint	Express Plus 2000 (EXPP-PL20##-CHIP)	Express Plus	DC	500	[CHIP sku]Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connctor including CCS, NACS, or CHAdeMO
ChargePoint	Express Plus 2000 (EXPP-PL20##-FHWA)	Express Plus	DC	500	[FHWA sku] Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connctor including CCS, NACS, or CHAdeMO
ChargePoint	Express Plus 2000 (EXPP-PL20##)	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connctor including CCS, NACS, or CHAdeMO
CyberSwitching	CSE1-WIFI-BL	CSE1	AC	11.5	Single Port
EnergiSpot	ATLEU2-50AAS	Level 2 AC Charger	AC	12	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simutaneous charging session.
EnergiSpot	ATLEU2-80AAS	Level 2 AC Charger	AC	19.2	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simutaneous charging session.
EnergiSpot	ATLUE2-32AAS	Level 2 AC Charger	AC	7.7	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simutaneous charging session.
Epic Charging	EC48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	EC80-AC	Epic80	AC	19.2	Single Port, Standalone network capability
Epic Charging	ECB48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	ECB80-AC	Epic80	AC	19.2	Single Port, Standalone network capability
EVBolt	EVB-AC-PAX19	Prestige 19	AC	19.1	Single Port, Standalone network capability
EverCharge	E800-1017-01	DCFC 240kW Power Cabinet	DC	240	OCA Full and Security certificates under software version 1.2009.0 (alternate company name on OCA cert - Wanbang Digital Energy Co., Ltd.)
EverCharge	E800-1029-01	DCFC 240kW Power Dispenser, w/Dual 200A CCS1	DC	240	OCA Full and Security certificates under software version 1.2009.0 (alternate company name on OCA cert - Wanbang Digital Energy Co., Ltd.)
EverCharge	E800-1042-01	DCFC 320kW All-in-One, w/ Dual CCS1	DC	320	Dual port.
EverCharge	EV002-48,E800-1000	EV02	AC	11.52	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-32A	EV02	AC	7.68	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-40A	EV02	AC	8.3	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001	EV02	AC	19.2	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001-40A	EV02	AC	8.3	Single Port, Standalone network capability
EvoCharge	EVC5001####	EVC5001####	AC	12	Single port.
EvoCharge	EVO32-310-001	iEVSE Plus 32	AC	7.7	Single Port, Standalone network capability
EvoCharge	EVO32-310-002	iEVSE Plus 32	AC	7.7	Dual Port, Standalone network capability
EvoCharge	EVO32-320-001	iEVSE 32	AC	7.7	Single Port, Standalone network capability
EvoCharge	EVO32-320-002	iEVSE 32	AC	7.7	Dual Port, Standalone network capability
EvoCharge	EVO80-###-###	MAX80	AC	19.2	
EvoCharge	W1-1962-#####	iEVSE	AC	9.6	
EVSIS	JC-94F2-350-0T5	DC Charger 350kW	DC	350	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-94F2-400-0T5	DC Charger 400kW	DC	400	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-100-CT	DC Charger 100kW	DC	100	CCS/CHAdeMO (optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-180-CT	DC Charger 180kW	DC	180	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-240-CT	DC Charger 240kW	DC	240	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
FLO	CoRe+ MAX	CoRe+™ MAX	AC	19.2	Single Port
FLO	CoRe+ STD 21 FT	CoRe+™	AC	7.2	Dual Port , Standalone network capability
FLO	SmartTWO	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	SmartTWO Cellular	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	SmartTWO For City Curbside	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	Ultra	Ultra	DC	320	Dual port.
Gravity	GR-LH500CX		DC	500	
Gravity	GT-AH200XX		DC	200	
Gravity	GT-AV200XX		DC	200	
Gravity	GT-LAV500EX		DC	500	
Gravity	GT-LLH500EX		DC	500	
Gravity	GT-LV500CX		DC	500	
Loop Global	EVS-32A-L2-001	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability
Loop Global	EVS-32A-L2-002	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability
Loop Global	EVS-80A-L2-001	EV-Fleet	AC	19.2	SAE J1772, Standalone network capability
Loop Global	EVS-80A-L2-002	EV-Fleet	AC	19.2	SAE J1772, Standalone network capability

Loop Global	EVS-FLASH-300-D01	Infinity Flash (with screen)	DC	300	Dual port with screen. Power cabinet required: EVS-FLASH- 360-PC01
Loop Global	EVS-FLASH-300-D01-150	Infinity Flash (with screen)(derated)	DC	150	150kW max per port
Loop Global	EVS-FLASH-300-D02	Infinity Flash (without screen)	DC	300	Dual port without screen. Power cabinet required: EVS-FLASH- 360-PC01
Loop Global	EVS-FLASH-300-D02-150	Infinity Flash (without screen)(derated)	DC	150	150kW max per port
Noodoe	AC11P/ AC11P Exceed		AC	11.5	Single port.
OpConnect	IC80	IC80	AC	19.2	Single Port NRTL Listed as EX-1193-1
OpConnect	OC-IC3-32AH		AC	7.2	Single Port, Standalone network capability
OpConnect	OC-SC3-32AN		AC	7.7	Single Port, Standalone network capability
OpConnect	SC80	SC80	AC	19.2	Single Port NRTL Listed as EX-1193-3
PowerPump	AC550	AC550	AC	10	Single Port.
Sinexcel	SEC1000/160Y-H-U ; SEC1000/160Y-T-U ; SEC1000/160Y-HH-U ; SEC1000/160Y-TT-U ; SEC1000/160Y-HT-U ; SEC1000/120Y-H-U ; SEC1000/120Y-T-U ; SEC1000/120Y-HH-U ; SEC1000/120Y-TT-U ; SEC1000/120Y-HT-U ; SEC1000/60Y-C-U ; SEC1000/60Y-S-U ; SEC1000/60Y-CC-U ; SEC1000/60Y-SS-U ; SEC1000/60Y-SC-U ;	SEC160	DC	160	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/240Y-H-U SEC1000/240Y-HH-U SEC1000/240Y-HJ-U SEC1000/240Y-T-U SEC1000/240Y-HT-U SEC1000/240Y-TJ-U SEC1000/240Y-TT-U	SEC 240	DC	240	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/360F-N-U SEC1000/480F-N-U SEC1000/200U-C-U SEC1000/200U-CC-U SEC1000/200U-CJ-U SEC1000/300U-H-U SEC1000/300U-HH-U SEC1000/300U-HC-U SEC1000/300U-HJ-U SEC1000/500U-F-U SEC1000/500U-FH-U SEC1000/500U-FC-U SEC1000/500U-FJ-U SEC1000/300U-T-U SEC1000/300U-TJ-U SEC1000/300U-HT-U SEC1000/300U-TT-U SEC1000/300U-TC-U SEC1000/500U-FT-U	SEC 480	DC	480	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Air cooling output 350A Liquid cooling sustained maximum output 500A
StarCharge	AC###AN030######	Artemis	AC	19.2	Single port.
StarCharge	DC3200AN147XYZ/ DC2800AN147XYZ/	Titan 320kW	DC	320	Dual port.
StarCharge	Neptune 240kW	Neptune 240kW	DC	240	OCA Full and Security certificates under software version 1.2009.0 (alternate company name on OCA cert - Wanbang Digital Energy Co., Ltd.)
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-WEVP1		AC	11.4	Single Port
TurnOnGreen	FSP1200/CPEVDC-120KW-#	FSP1200	DC	120	Single Port, CCS connector
TurnOnGreen	FSP600/CPEVDC-60KW-#	FSP600	DC	60	Single Port, CCS connector
Zerova	AXLU111001/AX48	AX48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Zerova	AXLU191001/AX80	AX80	AC	19.1	Single Port, Standalone network capability
Zerova	DQ480: DQWU482/DQWA482	DQ Series: DQ480	DC	480	Configurable to four or two cables
Zerova	DQWA242	DQ240	DC	240	Configurable to four or two cables
Zerova	DQWA360	DQ360	DC	360	Configurable to four or two cables
Zerova	DS120: DSWU122/DSWA122	DS Series: DS120	DC	120	1x CCS1 connector 1x CHAdeMO connector
Zerova	DS150: DSWU152/DSWA152	DS Series: DS150	DC	150	1x CCS1 connector 1x CHAdeMO connector
Zerova	DS180: DSWU182/DSWA182	DS Series: DS180	DC	180	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Zerova	DS60: DSWU601/DSWA601/SF##601	DS Series: DS60/SF60	DC	60	1x CCS1 connector 1x CHAdeMO connector
Zerova	DS90: DSWU901/DSWA901	DS Series: DS90	DC	90	1x CCS1 connector 1x CHAdeMO connector
Zerova	DT240: DTWA240	DT Series: DT240	DC	240	Configurable to four or two cables
Zerova	DZ480: DZWU482/DEZWA482	DZ Series: DZ480	DC	480	Configurable to two, four, or six cables

Network - Fleet

Brand	Network	Notes
AmpUp	AmpUp	

Autel	Autel Cloud	OCPP Full certificate for software version 2.0.105
Blink	Blink Network	
CHAEVI	CHAEVI	
ChargeLab	ChargeLab	
ChargePoint	ChargePoint Network	
Charli Charging	Charli Charging	
Electric Avenue	Electric Avenue	
Epic Charging	Epic Charging	
EV Connect	EVConnect	
EvoCharge	EvoCharge Network	
Gravity	Gravity Network	
Loop Global	Loop EV Charging Network	
Noodoe		OCPP Full certificate for software version v1.0.2
OpConnect	OpConnect Network	
PowerPump	PowerPump	
Wevo Energy	Wevo Energy	

Network - Commercial

Brand	Network	Notes
AmpUp	AmpUp	
Autel	Autel Cloud	OCPP Full certificate for software version 2.0.105
Blink	Blink Network	
CHAEVI	CHAEVI	
ChargeLab	ChargeLab	
ChargePoint	ChargePoint Network	
Charli Charging	Charli Charging	
Epic Charging	Epic Charging	
EV Connect	EVConnect	
OpConnect	OpConnect Network	
PowerPump	PowerPump	
Wevo Energy	Wevo Energy	